

01/07/00
JCS53 U.S. PTO

1-10-00
OSTROLENK, FABER, GERB & SOFFEN, LLP
Attorneys at Law
1180 Avenue of the Americas
New York, New York 10036-8403
(212) 382-0700

Telex
23 6925

Facsimile
(212) 382-0888

Cable
Ostrofaber NewYork

12
JCS25 U.S. PTO
09/479186
01/07/00

Express Mail #EL010283791US

Asst. Commissioner for Patents
Washington, DC 20231

OFGS File No. : P/3255-39
Inventor : Wayne DUPONT, Richard Rinehart & John McManus
Title : DYNAMIC UMBILICALS WITH INTERNAL STEEL RODS
Assignee : Coflexip


Enclosed herewith please find the following documents in the above-identified application for United States Letters Patent:


- 11 Pages of Specification including Abstract and Claims
- 11 Numbered Claims Calculated as 11 Claims for Fee Purposes
- 1 Sheet of Drawing Containing Figures 1 to 2. (Informal)
- X Declaration and Power of Attorney (Unsigned)
- Priority is Claimed under 35 U.S.C. §119:
- Convention Date _____ for _____ Appln. S.N. _____
- _____ Certified Priority Application
- _____ Verified Statement Claiming Small Entity Status under 37 C.F.R. §1.27.
- _____ Assignment
- X PTO-1449 & References
- X Return-Addressed Post Card

OFGS Check No. 90745, including the fee of \$690.00, calculated as follows:
Basic Filing Fee: \$ 690.00
Additional Filing Fees:
Total Number of Claims in Excess of 20, times \$18: 0
Number of Independent Claims in Excess of 3, times \$78: 0
One or More Multiple Dependent Claims: Total \$260. 0
Total Filing Fees or 690.00
Total Filing Fee Reduced 50% for Small Entity: 0
Assignment Recording Fee: \$40 0
TOTAL Filing Fee and Assignment Recording Fee: \$ 690.00

In the event the actual fee is greater than the payment submitted or is inadvertently not enclosed, or if any additional fee during the prosecution of this case is not paid, the Patent and Trademark Office is authorized to charge the underpayment to Deposit Account No. 15-0700.

EXPRESS MAIL CERTIFICATE
I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee (mail label #EL010283791US) in an envelope addressed to: Asst. Commissioner for Patents, Washington, D.C. 20231, on January 7, 2000

Respectfully submitted,

James A. Finder
Registration No.: 30,173
OSTROLENK, FABER, GERB & SOFFEN, LLP
1180 Avenue of the Americas
New York, New York 10036-8403
Telephone: (212) 382-0700

DOROTHY JENKINS
Name of Person Mailing Correspondence

Signature
January 7, 2000
Date of Signature

- 1 -

DYNAMIC UMBILICALS WITH INTERNAL STEEL RODSBACKGROUND OF THE INVENTIONField of the Invention

5 The present invention relates to improvements in umbilicals, particularly steel umbilicals for use in dynamic applications such as in risers.

Background Art

10 An umbilical consists of a group of one or more types of elongated active umbilical elements, such as electrical cables, optical fiber cables, or hoses, cabled together for flexibility and over-sheathed and/or armored for mechanical strength and ballast.

15 Umbilicals are used for transmitting power, signals and fluids (fluid injection, hydraulic power, gas release, etc.) to and from a subsea installation via the various elongated umbilical elements. An increasingly important use of umbilicals is the transmission of electrical power to electrical devices on the seabed, and depths of up to 6000 feet (2000 meters) are becoming common.

20 Generally, the elements are arranged within the umbilical as symmetrically as possible. The cross-section is preferably circular. In order to fill the interstitial voids between the various umbilical elements and obtain the desired circular configuration, filler components may be included within the voids (see the API specification, cited below, at pages 12-14).

 Umbilicals have to be able to withstand substantial laying and service loads and load combinations, and perform their functions for an extended design life, typically 25 years.

Electrical and/or optical fiber cables are not designed to resist the loads applied to the umbilical. These hoses and tubes, generally made of thermoplastic material or steel, are designed merely to resist collapse.

5 The umbilical elements are generally wound together in the well-known S-Z configuration (API, page 42). Then this bundle is over-sheathed. Since the S-Z configuration cannot withstand substantial tensile stress without unwinding, additional layers of armoring (steel or Kevlar, for example) must be wound counter-helically around this bundle. Then an external thermoplastic sheath is applied (API, pages 43-44).

10 A steel tube umbilical is defined as an umbilical wherein all or most of the elongated umbilical elements which compose the umbilical are made of steel tubes. The steel tubes and the other elongated umbilical elements that make up the umbilical are wound in a helical pattern around a central core. The core may be a flexible plastic tube, a larger steel tube, or one of the elongated umbilical elements.
15 The steel tubes are plastically deformed by the winding and do not unwind. With the helically wound steel tubes, such an umbilical under normal conditions (such as static applications and/or use at moderate water depth) will be able to withstand the moderate loads to be applied to it without the addition of substantial armoring layers.

20 However, under severe conditions (such as use in deep water and/or in dynamic applications), increased loads will be applied to the umbilical, due to the weight of the umbilical and to the dynamic movement of water. Strengthening elements and ballast elements have to be added to the umbilical to withstand these loads. The API specification suggests adding several external layers of armoring wires wound helically around the umbilical. This measure, however, leads to an
25 increase in the external diameter of the umbilical and a corresponding increase in the hydrodynamic load (see for example cross-section E-3.7 in the API Specification).

Fig. 1 is a cross-section of a conventional steel tube dynamic umbilical. This umbilical comprises a central core 1. The central core 1 may be

made of steel for transporting fluid. Or, for transporting electrical power, for example, the core may be made of metallic strand over-sheathed with a thermoplastic material. Disposed around the core are three steel tubes 2 for transporting fluid; two optical fiber cables 4; two armored electric power and/or signaling bundles 5; two thermoplastic fillers 6; and a sheath 8. Surrounding the sheath 8 is at least a pair of counter-helically wound armoring wires 12 and an outer sheath 14 of the type described in the API and in the '921 patent (discussed below).

The steel tubes, optical fiber cables, bundles and fillers are stranded together around the central core by means of a vertical helix machine. A suitable vertical helix machine is described in Bryant et al., "Duco, Inc., Umbilical Manufacturing Plant, Current & Future Capabilities," published in Houston at the Energy Week Conference, 1997 incorporated by reference. The resulting bundle is then coated.

The thermoplastic fillers fill the interstices between the several components of the umbilical in order to provide a circularly symmetrical arrangement.

The steel tubes are designed to resist collapse pressure and also to resist moderate tensile loading. The outside armor layers 12 provide additional strength and ballast.

The steel tubes may be made of carbon steel or stainless steel, for example. If they are made of carbon steel, they should be thermoplastic coated or zinc coated in order to provide acceptable corrosion resistance.

The outer sheath can be made by extrusion of thermoplastic (such as polyethylene) or may be woven (e.g., polypropylene yarn). It is also known to include sacrificial anodes within an umbilical, as shown for example in U.S. patent 5,362,921 owned by Alcatel STK), incorporated by reference. Sacrificial anodes 4 and 5, made of zinc, are arranged in between the steel tubes 3. Substantially the only function of these sacrificial anodes is to act in combination with the galvanized steel core member (1, 2) to protect the umbilical from corrosion. They do not absorb any substantial tensile loading or increase the weight of the umbilical. On the contrary,

the '921 patent teaches that the way to strengthen the umbilical is to add two layers of armor wires (7, 8) in the outer part of the umbilical.

API (American Petroleum Institute) Specification 17E, "Specification for Subsea Production Control Umbilicals" (September 1998), incorporated by reference, provides standards for the design and manufacture of umbilicals. There is no standard for steel tube umbilicals at this moment but a standard ISO CD 13628-5 (current version incorporated by reference) concerning both conventional API 17E and steel tube umbilicals is in progress and will be issued in mid-2000.

In order to achieve the requirements for use under severe conditions, it would be conceivable to increase the wall thickness of the tubes. However, increasing the wall thickness of the steel tubes entails the following drawbacks:

- the flexibility of the umbilical is reduced.
- the manufacture of the umbilical becomes more difficult or even impossible.

In order to avoid the above drawbacks the conventional measure as discussed above is to add additional layers of armoring for ballast. But adding armoring layers to the umbilical brings with it the following additional drawbacks:

- the outer diameter of the umbilical increases, which leads to an increase in the hydrodynamic drag area.
- the manufacturing cost increases, since an armoring machine is needed for the armor layers and the number of manufacturing passes is increased as well.

SUMMARY OF THE INVENTION

The present invention is adapted to address the foregoing drawbacks, specifically in dynamic or deep-water applications where additional armoring layers are conventionally added to the umbilical (deepwater, high tensile load, ballast). In an umbilical according to an important feature of the invention, one or more steel

rods, which provide strength and ballast, are wound helically within the umbilical along with the steel tubes and/or elongated active umbilical elements.

Advantageously these steel rods replace some or all of the thermoplastic filler elements that would otherwise be included within the umbilical. Thus, the invention avoids the need to apply additional armoring layers to the outside of the umbilical for strength and ballast.

Other features and advantages of the present invention will become apparent from the following description of embodiments of the invention, with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view of a conventional umbilical; and

Fig. 2 is a cross-sectional view of an umbilical according to an embodiment of the invention.

DETAILED DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

Fig. 2 is a cross-sectional view of a dynamic umbilical, for example for use as a riser, according to an embodiment of the invention. The respective fluid-carrying and other conduits in the umbilical of Fig. 2 correspond to those in Fig.1. Unnecessary redundant description of those elements will be omitted.

In order to provide an improved, smaller umbilical for dynamic application, with excellent stability, high tensile resistance and fatigue resistance, the thermoplastic fillers in the umbilical of Fig. 1 have been replaced with three solid steel rods 10 which in this embodiment have a diameter of 20 mm. These steel rods are designed to absorb the tensile loading and to ballast the umbilical. In order further to increase the weight, small solid steel rods 9, which may be about 8 mm in diameter, are also added, in the periphery of the bundle. With this arrangement, the

steel rods act as both tension and ballast elements and the need of an outer layer of armoring is avoided.

The steel rods 9, 10 may be made of carbon steel or stainless steel, for example. A coating 11 is provided on the rods when needed for corrosion resistance.

5 The steel rods are substantially solid. In this context, “substantially solid” means that the steel rods may be completely solid, or may be dense enough to provide enough weight to obtain the advantages of the invention.

10 In prior art dynamic umbilicals, it was conventional to add two layers of armoring wires, for example, and additional thermoplastic sheathing, in order to increase the strength and weight of the umbilical when necessary. These additional layers could increase the outside diameter of the umbilical by 20% for example. As an example, the umbilical of Fig. 1 will have an external diameter of about 100 mm. By comparison, the embodiment of the invention shown in Fig. 2 will have an external diameter of only about 80 mm.

15 The hydrodynamic drag of an umbilical in moving water is determined by the following formula:

$$D = \rho \cdot C_d \cdot D \cdot \frac{U^2(t)}{2}$$

wherein: ρ is the density of water;

20 C_d is the drag coefficient;

$U(t)$ is the velocity of the water (current, wave, etc.); and

D is the diameter of the umbilical.

Consequently, the umbilical diameter is increased by 20%, the hydrodynamic drag is also increased by 20%. Thus, when the hydrodynamic drag area is
25 substantial, it is necessary either to increase the tension in the dynamic umbilical or to add yet another layer of armoring to further increase the weight in order to stabilize the umbilical. These disadvantages are avoided by the present invention, in

which internal steel rods can be used, to provide additional weight and stability without increasing the diameter of the umbilical.

The main advantages of this design are the following:

- 5 – The use of steel rods in combination with metal tubes increases the tensile capacity of an umbilical, allowing installation and continuous dynamic use in deeper water.
- The steel rods reduce the stress in the steel tubes which results in increased service life of the umbilical.
- 10 – The steel rods also increase the mass of the umbilical without increasing the external diameter and consequently the hydrodynamic drag area of the umbilical, which results in reduced dynamic riser excursions, and in turn prevents interference with other objects.
- Since the steel rods are sufficient for absorbing the tensile loading, the conventional steel tubes in the umbilical can be designed merely to resist
- 15 collapsing pressure only, resulting in a decrease in the wall thickness of the tube and consequently a decrease in manufacturing cost.
- The steel rods are assembled in the same manufacturing pass as the conventional steel tubes, which avoids the need of an additional manufacturing process for armoring, and consequently the need for an
- 20 armoring machine.

The invention can be used both in static, deepwater applications when substantial loading is to be applied to the umbilical, and in dynamic applications when the umbilical is too light and ballast is needed.

25 Any number of steel rods can be provided in order to obtain the benefits of the invention, the only limitation being the amount of empty space available given the conduits, steel tubes and other elements needed in the umbilical.

Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will

00435806.3

WHAT IS CLAIMED IS:

1. An umbilical comprising:
a plurality of steel tubes helically wound around a core; and
at least one substantially solid steel rod helically wound around said core,
said steel rod being arranged in a void between said steel tubes..
2. The umbilical of claim 1, further comprising at least one elongated
umbilical element selected from the group consisting of thermoplastic tubes, optical
fiber cables, and electrical power and communications cables.
3. The umbilical of claim 2, further comprising a non-metallic outer sheath
surrounding and in direct contact with at least some of said plurality of steel tubes
and said elongated umbilical elements.
4. The umbilical of claim 3, wherein said at least one steel rod is in direct
contact with said non-metallic outer sheath.
5. The umbilical of claim 1, wherein said at least one steel rod is made of
solid steel.
6. A method of increasing the hydrodynamic stability of an umbilical
comprising a plurality of steel tubes helically wound around a core,
said method comprising the step of arranging at least one substantially solid
steel rod in a void between said steel tubes and helically wound around said core.
7. The method of claim 6, further comprising the step of helically winding
around said core at least one elongated umbilical element selected from the group

consisting of thermoplastic tubes, optical fiber cables, and electrical power and communications cables.

8. The method of claim 7, further comprising the step of placing a non-metallic outer sheath surrounding and in direct contact with at least some of said plurality of steel tubes and said elongated umbilical elements.

9. The method of claim 8, further comprising the step of placing said at least one steel rod in direct contact with said non-metallic outer sheath.

10. The method of claim 6, comprising the step of making said at least one steel rod of solid steel.

11. The method of claim 6, wherein said umbilical further comprises at least one plastic filler helically wound around said core with said steel tubes,

said method comprising the step of replacing said at least one plastic filler with said at least one steel rod.

DYNAMIC UMBILICALS WITH INTERNAL STEEL RODSABSTRACT OF THE DISCLOSURE

In an umbilical, one or more steel rods, which provide strength and ballast, are wound helically within the umbilical along with the steel tubes and/or elongated active umbilical elements. These steel rods replace some or all of the thermoplastic filler elements that would otherwise be included within the umbilical. An umbilical according to an embodiment of the invention may comprise a plurality of steel tubes helically wound around a core, and at least one substantially solid steel rod helically wound around the core, the steel rod being arranged in a void between the steel tubes. Thus, the invention avoids the need to apply additional armoring layers to the outside of the umbilical for strength and ballast.

Fig 1
PRIOR ART





Fig 2



00479185-010200

UNITED STATES OF AMERICA
COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

OFPS FILE NO.
P/3255-39

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

DYNAMIC UMBILICALS WITH INTERNAL STEEL RODS

the specification of which is attached hereto, unless the following box is checked:

☐ was filed on _____ as United States patent Application Number or PCT International patent application number _____ and was amended on _____ (if any).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.
I acknowledge the duty to disclose all information known to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate or United States provisional application(s) listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign or Provisional Application(s)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			YES ___ NO ___
			YES ___ NO ___
			YES ___ NO ___

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

UNITED STATES APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby appoint customer no. 2352 OSTROLENK, FABER, GERB & SOFFEN, LLP, and the members of the firm, Samuel H. Weiner - Reg. No. 18,510; Jerome M. Berliner - Reg. No. 18,653; Robert C. Faber - Reg. No. 24,322; Edward A. Meilman - Reg. No. 24,735; Stanley H. Lieberstein - Reg. No. 22,400; Steven I. Weisburd - Reg. No. 27,409; Max Moskowitz - Reg. No. 30,576; Stephen A. Soffen - Reg. No. 31,063; James A. Finder - Reg. No. 30,173; William O. Gray, III - Reg. No. 30,944; Louis C. Dujmich - Reg. No. 30,625 and Douglas A. Miro - Reg. No. 31,643, as attorneys with full power of substitution and revocation to prosecute this application, to transact all business in the Patent & Trademark Office connected therewith and to receive all correspondence.

SEND CORRESPONDENCE TO: **OSTROLENK, FABER, GERB & SOFFEN, LLP** DIRECT TELEPHONE CALLS TO:
1180 AVENUE OF THE AMERICAS (212) 382-0700
NEW YORK, NEW YORK 10036-8403
CUSTOMER NO. 2352

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF SOLE OR FIRST INVENTOR Wayne DUPONT		INVENTOR'S SIGNATURE	DATE
RESIDENCE (City and either State or Foreign Country) Houston, Texas 77008		COUNTRY OF CITIZENSHIP U.S.A.	
POST OFFICE ADDRESS 1015 Arlington Street, Houston, Texas 77008			
FULL NAME OF SECOND JOINT INVENTOR (IF ANY) Richard RINEHART		INVENTOR'S SIGNATURE	DATE
RESIDENCE (City and either State or Foreign Country) Webster, Texas 77598		COUNTRY OF CITIZENSHIP U.S.A.	
POST OFFICE ADDRESS 450 Eldorado Blvd. #701, Webster, Texas 77598			
FULL NAME OF THIRD JOINT INVENTOR (IF ANY) John MCMANUS		INVENTOR'S SIGNATURE	DATE
RESIDENCE (City and either State or Foreign Country) Houston, Texas 77079		COUNTRY OF CITIZENSHIP U.S.A.	
POST OFFICE ADDRESS 13610 Kingsride In, Houston, Texas 77079			

☐ CONTINUED ON PAGE 2